
Product Code: **S06307512-3090-35D**

FANGSHAO Series Recessed



Specifications

Material	**Aluminium**
Finish / Colour	BK / WH / CR / GB
Overall Dimensions	**Ø80 × 98 mm**
Recess Opening	**Ø75 mm**
Weight	
Protection Grade	**IP54**
Labelling	

Electrical Specifications

Power Supply Unit	**Not included**
Control	**Constant current power supply not included**
Constant Current Supply	**300 mA**
Insulation Class	

Light Source

Type of Source	**1202**

Current (mA)	Flux (lm)	Power (W)	Efficacy (lm/W)	Vf min
300	947	10.05	94.2	33.5

Colour Temperature				**3000K**
Colour Rendering Index (Ra)				**90**
IES-TM-30	IFidelity Index Rf	**91**	Gamut Index Rg	**98**
Standard Deviation Colour Matching (SDCM)				**3**
Blue Light Risk Group				**RG1**
Average Life (Ta 25°)				**50,000 h L80 B10**
Light Source Replaceability				**LED replaceable by qualified professional**

Optical System


Lens Material	**Polymethyl Methacrylate**
Lens Finish	**Transparent**

Photometric Data

Downward Flux Fraction DFF (%)	**100 %**
Luminous Beam Angle	**35°**

Current — **300 mA** | Luminaire Flux: **947 lm**

3000K



Beam Angle:35°

Luminaire Flux 947 lm

H(m)	E(lx)	D(cm)
1	2687	62
2	672	123
3	299	185
4	168	247
5	108	308

YUANFENG ®copyright The material can not be modified, copied, reproduced or transferred neither used improperly . More information, please log in **www.yoflighting.com**