

Product Code: **S07305509-2790-36D**

GUAN Series Recessed





Specifications

Material	**Aluminium**
Finish / Colour	BK / WH
Overall Dimensions	**Ø60 × 87 mm**
Recess Opening	**Ø55 mm**
Weight	
Protection Grade	**IP54**
Labelling	

Electrical Specifications

Power Supply Unit	**Not included**
Control	**Constant current power supply not included**
Constant Current Supply	**200 mA**
Insulation Class	

Light Source

Type of Source	**1201**

Current (mA)	Flux (lm)	Power (W)	Efficacy (lm/W)	Vf min
200	504	6.7	75.2	33.5

Colour Temperature				**2700K**
Colour Rendering Index (Ra)				**90**
IES-TM-30	IFidelity Index Rf	**93**	Gamut Index Rg	**98**
Standard Deviation Colour Matching (SDCM)				**3**
Blue Light Risk Group				**RG1**
Average Life (Ta 25°)				**50,000 h L80 B10**
Light Source Replaceability				**LED replaceable by qualified professional**

Optical System


Lens Material	**Polymethyl Methacrylate**
Lens Finish	**Transparent**

Photometric Data

Downward Flux Fraction DFF (%)	**100 %**
Luminous Beam Angle	**36°**

Current — **200 mA** | Luminaire Flux: **504 lm**

2700K



Beam Angle:36°

Luminaire Flux 504 lm

H(m)	E(lx)	D(cm)
1	1521	63
2	380	126
3	169	189
4	95	252
5	61	316

YUANFENG ®copyright The material can not be modified, copied, reproduced or transferred neither used improperly

More information, please log in **www.yoflighting.com**