

Product Code: **TS07305509-3597-18D**

# GUAN Series Recessed




## Specifications

| | |
|---|---|
| Material | **Aluminium** |
| Finish / Colour | BK / WH |
| Overall Dimensions | **Ø80 × 87 mm** |
| Recess Opening | **Ø55 mm** |
| Weight | |
| Protection Grade | **IP54** |
| Labelling | CE |

## Electrical Specifications

| | |
|---|---|
| Power Supply Unit | **Not included** |
| Control | **Constant current power supply not included** |
| Constant Current Supply | **200 mA** |
| Insulation Class | |

## Light Source

| Type of Source | **1201** |
|---|---|

| Current (mA) | Flux (lm) | Power (W) | Efficacy (lm/W) | Vf min |
|---|---|---|---|---|
| 200 | 356 | 6.7 | 53.1 | 33.5 |

| | |
|---|---|
| Colour Temperature | **3500K** |
| Colour Rendering Index (Ra) | **97** |
| IES-TM-30 IFidelity Index Rf **95** Gamut Index Rg | **101** |
| Standard Deviation Colour Matching (SDCM) | **3** |
| Blue Light Risk Group | **RG1** |
| Average Life (Ta 25°) | **50,000 h L80 B10** |
| Light Source Replaceability | **LED replaceable by qualified professional** |

## Optical System


| | |
|---|---|
| Lens Material | **Polymethyl Methacrylate** |
| Lens Finish | **Transparent** |

## Photometric Data

| | |
|---|---|
| Downward Flux Fraction DFF (%) | **100 %** |
| Luminous Beam Angle | **18°** |

Current — **200 mA** | Luminaire Flux: **356 lm**

## 3500K




Beam Angle:18°

Luminaire Flux 356 lm

| H(m) | E(lx) | D(cm) |
|---|---|---|
| 1 | 3543 | 32 |
| 2 | 886 | 63 |
| 3 | 394 | 95 |
| 4 | 222 | 127 |
| 5 | 142 | 158 |


YUANFENG ®copyright The material can not be modified, copied, reproduced or transferred neither used improperly . More information, please log in **www.yoflighting.com**