
Product Code: **TRS88307228-3590-26D**

TRACKO Series Track-Mounted



Specifications

Material	**Aluminium**
Finish / Colour	BK / WH
Overall Dimensions	**Ø72 × 108 mm**
Mounting Type	**Track Mounted**
Weight	
Protection Grade	**IP20**
Labelling	

Electrical Specifications

Power Supply Unit	**Included**
Control	**Constant current power supply included**
Constant Current Supply	**700 mA**
Insulation Class	**Class I**

Light Source

Type of Source	**13C**

Current (mA)	Flux (lm)	Power (W)	Efficacy (lm/W)	Vf min
700	2747	23.59	116.4	33.7

Colour Temperature				**3500K**
Colour Rendering Index (Ra)				**90**
IES-TM-30	IFidelity Index Rf	**91**	Gamut Index Rg	**100**
Standard Deviation Colour Matching (SDCM)				**3**
Blue Light Risk Group				**RG1**
Average Life (Ta 25°)				**50,000 h L80 B10**
Light Source Replaceability				**LED replaceable by qualified professional**

Optical System


Lens Material	**Polymethyl Methacrylate**
Lens Finish	**Transparent**

Photometric Data

Downward Flux Fraction DFF (%)	**100 %**
Luminous Beam Angle	**26°**

Current — **700 mA** | Luminaire Flux: **2747 lm**

3500K



Beam Angle:26°

Luminaire Flux 2747 lm

H(m)	E(lx)	D(cm)
1	13033	47
2	3258	94
3	1448	142
4	815	189
5	521	236

YUANFENG ®copyright The material can not be modified, copied, reproduced or transferred neither used improperly . More information, please log in **www.yoflighting.com**