

Product Code: **S07507520-4097-27D**

VON Series Recessed





Specifications

Material	**Aluminium**
Finish / Colour	BK / WH / CR / GB
Overall Dimensions	**Ø82 × 122 mm**
Recess Opening	**Ø75 mm**
Weight	
Protection Grade	**IP54**
Labelling	CE

Electrical Specifications

Power Supply Unit	**Not included**
Control	**Constant current power supply not included**
Constant Current Supply	**500 mA**
Insulation Class	

Light Source

Type of Source	**1204**

Current (mA)	Flux (lm)	Power (W)	Efficacy (lm/W)	Vf min
500	1733	15.7	110.4	31.4

Colour Temperature	**4000K**
Colour Rendering Index (Ra)	**97**
IES-TM-30 IFidelity Index Rf **92** Gamut Index Rg	**98**
Standard Deviation Colour Matching (SDCM)	**3**
Blue Light Risk Group	**RG1**
Average Life (Ta 25°)	**50,000 h L80 B10**
Light Source Replaceability	**LED replaceable by qualified professional**

Optical System


Lens Material	**Polymethyl Methacrylate**
Lens Finish	**Transparent**

Photometric Data

Downward Flux Fraction DFF (%)	**100 %**
Luminous Beam Angle	**27°**

Current — **500 mA** | Luminaire Flux: **1733 lm**

4000K



Beam Angle:27°

Luminaire Flux 1733 lm

H(m)	E(lx)	D(cm)
1	8156	49
2	2039	97
3	906	146
4	510	195
5	326	244

YUANFENG ®copyright The material can not be modified, copied, reproduced or transferred neither used improperly . More information, please log in **www.yoflighting.com**